


ARMANO



# Mechanical Pressure Measurement

## Bourdon tube pressure gauges



## Quality Made in Germany

### Mechanical Pressure Measurement

The ARMANO Messtechnik GmbH represents tradition and innovation in the production and distribution of precision pressure and temperature measuring instruments, which have an excellent reputation worldwide – for more than 100 years.

We are continually developing customer-specific solutions for a variety of applications requiring pressure and temperature measuring technology. Their use is manifold and there are always new applications.

Mechanical pressure gauges are indicating pressure measuring instruments for gauge, absolute and differential pressure.

For the optimal solution of various applications, we distinguish between the following product categories: Bourdon tube pressure gauges, Bourdon tube test gauges, diaphragm pressure gauges (horizontal / vertical diaphragm), duplex and differential pressure gauges and capsule gauges for low pressure.

In this brochure, you will find our standard range of mechanical pressure measuring instruments from our product range Bourdon tube pressure gauges, including additional electrical accessories.

Your instrument is not listed here?

Jointly, we will find a suitable solution for your application.

Do not hesitate to contact us!

Applications	4
General Features	5
Metrological Information	7
Dial / Standard Scales / Scale Division	8
Certificates and Approvals	9
Standard Pressure Gauges	10
Special Pressure Gauges	13
Low Cost Pressure Gauges	16
Chemical Seal Mounting	17
Additional Electrical Accessories	18
Service	19

## Our Products at a Glance



**Mechanical Pressure Measurement**



**Electronic Pressure Measurement**



**Chemical Seal Mounting**



**Calibration Technology**



**Mechanical Temperature Measurement**



**Electrical Temperature Measurement**



**Thermowells & Accessories**

# Applications

Bourdon tube pressure gauges are suitable for the measurement of positive and negative overpressures between 0 – 0.6 and 0 – 6000 bar for liquid or gaseous media. The information given in DIN EN 837-2 have to be considered for the selection of the suitable measuring instrument. In particular, it has to be ensured that the medium does not corrode any of the wetted parts.

## Fields of Application

Our high-quality pressure gauges are applicable in a wide range of fields. With our impressive customer solutions for various industries, we show you which ones are suitable for you!

Chemistry & Petrochemistry




Engineering




Oil and Gas



Energy




Shipbuilding Industry



Rail Cars



Building Services and Refrigeration Engineering



## Customer Solutions

Numerous customer solutions are available for almost all models. Thus, only a few examples are specified below. Further possibilities can be found in the data sheets or other technical documents of the respective models. Further individual special configurations are available upon request.

No matter what requirements and needs your application has, together with our technicians we will find an ideal solution for you – please contact us!



## General Features

### Selection Criteria

A detailed description of the selection criteria can be found in the commentary of the DIN e. V. "Überdruckmessgeräte nach DIN EN 837" ("Overpressure measuring instruments according to DIN EN 837", available in German only), published by the Beuth Verlag. Please compare the selection criteria for pressure gauges described in our operating instruction, which can be found as pdf file on our website.

#### Standard Material Combinations

##### (for the wetted parts)

Depending on the process, a wide range of materials are applied to meet the demands on temperature resistance, mechanical strength and chemical resistance. Additionally, we provide particularly economic, material-saving construction types for special materials. There, only the wetted parts are made of the special material.

Ordering code	Pressure ranges	Connection	Bourdon tube
- 1		brass	bronze
	high ranges	brass	stainless steel 316L
- 3		stainless steel 316L	stainless steel 316L
	high ranges	stainless steel 316L	NiFe alloy
- 6	for almost all models	Monel	Monel

#### Process Connections

With only a few exceptions, our Bourdon tube pressure gauges are available with the following process connections according to DIN EN 837-1:

- ◆ G ¼ B (¼" BSP) up to NCS 63
- ◆ G ½ B (½" BSP) from NCS 80

Almost all models are available with the following connections without any extra charges:

- ◆ ¼" NPT or M 12x1.5 up to NCS 63
- ◆ ½" NPT or M 20x1.5 from NCS 80

Please note:

Process connection G ¼ B, ¼" NPT and M 12x1.5 according to DIN EN 837-1

max. pressure range 600 bar (type – 1)  
1000 bar (type – 3)

Further versions are available as customised product.


#### Pressure Ranges

Bar is the preferred pressure unit according to DIN EN 837-1. In this model overview, the available pressure ranges are indicated in bar. Beyond that, there are several further pressure units available, e.g. psi, mmWS, kg/cm<sup>2</sup>, kPa, MPa.

Multiple scales are available as well.

Special scales can be manufactured upon request.

For applications in refrigeration engineering, our pressure gauges can be provided with temperature scales for the different refrigerants.



#### Case Fillings

Case fillings are applied for difficult operating conditions, such as vibrations and high pressure variations or to avoid condensation (outdoor installations). The standard filling liquid is glycerin (models ...G) or a special oil for pressure gauges with mounted additional electrical accessory (models ...Oe). For lower temperatures, silicone oil is used.

For further details on temperature limitations, see page 7.



## General Features

### Construction

The measuring systems of Bourdon tube pressure gauges are designed regardless of measurand and pressure range. Each measuring system has a socket with process connection on the one side and connection of the measuring element (Bourdon tube) on the other side. Depending on the nominal pressure, this Bourdon tube is designed in circular form (for smaller nominal pressures) or in helical form (for higher nominal pressures). The movement transmits the motion of the measuring element, which is proportional to the pressure, into a rotary pointer motion, enabling the pressure to be indicated on the scale of the dial. These components form a constructional unit ready for measurement. Case, ring and window serve as protection against external influences.

**Bourdon Tube Measuring System, Circular Form**



**Media**

for gaseous and liquid media

**Bourdon Tube Measuring System, Helical Form**



**Pressure Ranges**

from 0 – 0.6 bar to 0 – 6000 bar

# Metrological Information

## Accuracy according to DIN EN 837-1 and DIN 16001

The scope of both standards depends on the pressure range of the Bourdon tube pressure gauge. DIN EN 837-1 applies to instruments with pressure ranges up to 1600 bar. For pressure ranges over 1600 bar, DIN 16001 is to be applied.

### DIN EN 837-1

According to DIN EN 837-1, the accuracy class includes the combination of the error variables non-linearity, hysteresis and friction. The maximum permissible measurement error applies to each measuring point within the pressure range. In addition, DIN EN 837-1 specifies that the hysteresis error at each measuring point must not exceed the value of the accuracy class, i.e. the hysteresis must not exceed 50 % of the permissible error band.

- ◆ Class 1.6 up to NCS 80
- ◆ Class 1.0 from NCS 100

### DIN 16001

DIN 16001 specifies the accuracy class in the same way except that the hysteresis error at each measuring point must not exceed twice the value of the accuracy class, i.e. each measuring point must be within the tolerance band and the hysteresis may cover the entire width of the error band.

Please regard possible limitations in the data sheets!

## Load Limits

To guarantee a long service life, the pressure range should be selected in a way to ensure that the pressure load does not exceed 75 % of the full scale value for steady loads or 60 % of the full scale value for dynamic loads.

It is also recommended not to use the initial range (up to approx. 20 %) of the pressure gauge for measurements, because there the permissible measurement deviation is the largest in relation to the measured value.

The following maximum load limits are to be regarded:

According to DIN EN 837-1			According to DIN 16001	
Nominal case sizes	100, 125, 160, 250, 4 1/2" and 96 x 96, 144 x 144	40, 50, 63, 80	100, 160	
at steady load	full scale value	75 % of the full scale value	75 % of the full scale value	
max. permissible overpressure	1.3-times measuring span	full scale value	full scale value	

## Temperature Limitations

◆ Medium temperature:

Ordering code	Case	Joint	Unfilled	Filled
- 1		soft soldered	+60 °C (+140 °F)	+60 °C (+140 °F)
		silver brazed	+100 °C (+212 °F)	+100 °C (+212 °F)
	plastic	silver brazed		+70 °C (+158 °F)
- 3	stainless steel		+200 °C (+392 °F)	+100 °C (+212 °F)
	plastic		+100 °C (+212 °F)	+70 °C (+158 °F)

- ◆ Storage temperature:
  - for glycerin filling -40 / +70 °C (-40 / +158 °F)
  - for glycerin filling -20 / +70 °C (-4 / +158 °F)
  - for silicone filling -20 / +60 °C (-4 / +140 °F)

◆ Ambient temperature:

unfilled	standard	-40 / +60 °C (-40 / +140 °F)
	customised	-60 / +60 °C (-76 / +140 °F)
filled	standard	-20 / +60 °C (-4 / +140 °F)
	customised	-40 / +60 °C (-40 / +140 °F)

Please regard possible limitations in the data sheets. Please contact us if you require instruments with higher or lower temperature limitation.

- ◆ Reference temperature: +20 °C (+68 °F)

If the operating temperatures of the measuring system (resilient element and movement) deviate from the reference temperature, additional deviations of the pressure indication do occur. These can be up to 0.5 % of the span per 10 K.

# Dial / Standard Scales / Scale Division

Dial inscriptions, pressure range, scale divisions and figures on the scale are designed according to DIN EN 837-1 or DIN 16001. The standard dial is white with black inscription. Pressure gauges from NCS 80, to a great extent also NCS 63, are provided with a clearly identifiable instrument number on the dial.

Nominal Case Sizes 80, 100, 160, 250, 4 1/2", 96 x 96, 144 x 144	Pressure ranges according to DIN EN 837-1 in bar		Smallest subdivision of the scale (bar)	Pressure ranges in psi		Smallest subdivision of the scale (psi)	
	vacuum	-1200 / -1	0 mbar	20 mbar	-30" Hg / -30" Hg	0	-0.2" Hg
	-0.6 / -1	0	0.02		+15	-0.5" Hg / +0.2	
			0.01		+30	-1" Hg / +0.5	
compound range	-1 / -1	+0.6	0.05		+60	-1" Hg / +1	
	-1 / -1	+1.5	0.05		+100	-2" Hg / +1	
	-1 / -1	+3	0.1		+160	-5" Hg / +2	
	-1 / -1	+5	0.1		+200	-5" Hg / +2	
	-1 / -1	+9	0.2		+300	-10" Hg / +5	
	-1 / -1	+15	0.5				
pressure	0.2 - 0	1	0.02	3 - 0	15	0.2	
	0 - 0	0.6	0.01	0 - 0	10	0.1	
	0 - 0	1	0.02	0 - 0	15	0.1	
	0 - 0	1.6	0.05	0 - 0	30	0.2	
	0 - 0	2.5	0.05	0 - 0	60	0.5	
	0 - 0	4	0.1	0 - 0	100	1	
	0 - 0	6	0.1	0 - 0	160	2	
	0 - 0	10	0.2	0 - 0	200	2	
	0 - 0	16	0.5	0 - 0	300	2	
	0 - 0	25	0.5	0 - 0	400	5	
	0 - 0	40	1	0 - 0	600	5	
	0 - 0	60	1	0 - 0	800	10	
	0 - 0	100	2	0 - 0	1000	10	
	0 - 0	160	5	0 - 0	1500	10	
	0 - 0	250	5	0 - 0	2000	20	
	0 - 0	400	10	0 - 0	3000	20	
	0 - 0	600	10	0 - 0	4000	50	
	0 - 0	1000	20	0 - 0	5000	50	
	0 - 0	1600	50	0 - 0	6000	50	
	0 - 0	2500 <sup>1)</sup>	50	0 - 0	10000	100	
	0 - 0	4000 <sup>1)</sup>	100	0 - 0	15000	100	
	0 - 0	5000 <sup>1)</sup>	100	0 - 0	20000	200	
	0 - 0	6000 <sup>1)</sup>	100	0 - 0	30000	200	
				0 - 0	35000	200	
				0 - 0	40000	500	
				0 - 0	50000	500	
				0 - 0	60000	500	

Nominal Case Sizes 40, 50, 63	Pressure ranges according to DIN EN 837-1 in bar		Smallest subdivision of the scale (bar)	Pressure ranges in psi		Smallest subdivision of the scale (psi)	
						NCS 40, 50	NCS 63
vacuum	-1200 / -1	0 mbar	50 mbar	-30" Hg / -30" Hg	0	-1" Hg	-0.5" Hg
	-0.6 / -1	0	0.02		+15	-1" Hg / +0.5	-1" Hg / +0.5
			0.02		+30	-2" Hg / +1	-1" Hg / +0.5
compound range	-1 / -1	+0.6	0.05		+60	-5" Hg / +2	-2" Hg / +2
	-1 / -1	+1.5	0.1		+100	-5" Hg / +2	-5" Hg / +2
	-1 / -1	+3	0.1		+160	-10" Hg / +5	-5" Hg / +2
	-1 / -1	+5	0.2		+200	-10" Hg / +5	-10" Hg / +5
	-1 / -1	+9	0.2		+300	-10" Hg / +10	-10" Hg / +5
	-1 / -1	+15	0.5				
pressure	0.2 - 0	1	0.02	3 - 0	15	0.5	0.2
	0 - 0	0.6	0.02	0 - 0	10	0.2	0.1
	0 - 0	1	0.02	0 - 0	15	0.5	0.2
	0 - 0	1.6	0.05	0 - 0	30	1	0.5
	0 - 0	2.5	0.1	0 - 0	60	2	1
	0 - 0	4	0.1	0 - 0	100	2	1
	0 - 0	6	0.2	0 - 0	160	5	2
	0 - 0	10	0.2	0 - 0	200	5	2
	0 - 0	16	0.5	0 - 0	300	10	5
	0 - 0	25	1	0 - 0	400	10	5
	0 - 0	40	1	0 - 0	600	20	10
	0 - 0	60	2	0 - 0	800	20	10
	0 - 0	100	2	0 - 0	1000	20	10
	0 - 0	160	5	0 - 0	1000	50	20
	0 - 0	250	10	0 - 0	2000	50	20
	0 - 0	400	10	0 - 0	3000	100	50
	0 - 0	600	20	0 - 0	4000	100	50
	0 - 0	1000	20	0 - 0	5000	200	100
				0 - 0	6000	200	100
				0 - 0	10000	200	100
				0 - 0	15000	-	200

<sup>1)</sup> pressure ranges according to DIN 16001



# Certificates and Approvals

## Standards

Our company is certified according to the highest quality standards and our product portfolio meets the highest quality demands. We do not only manufacture according to product-specific instrument standards, we also offer versions with special approvals for application areas with specific requirements. The ARMANO Messtechnik GmbH is certified according to DIN EN ISO 9001.



**SIL 2**

**SIL 3**



## Standard Pressure Gauges

Comprehensive descriptions of available options and special versions for all models can be found in the respective data sheets. The latest versions of the documents are available for download on our website [www.armano-messtechnik.com](http://www.armano-messtechnik.com).




**RCh / RChG<sup>1)</sup>**

Case / ring	bayonet ring case stainless steel
Case filling	without / with
Accuracy	class 1.0
Nominal size	100, 160, 250 mm
Wetted parts	- 1 brass - 3 stainless steel 316L - 6 Monel
Pressure ranges	0 – 0.6 bar to 0 – 1600 bar
Data sheet	1201




**RChg / RChgG<sup>1)</sup>**

Case / ring	crimped-on ring case stainless steel
Case filling	without / with
Accuracy	class 1.0
Nominal size	100, 125, 160 mm
Wetted parts	- 1 brass - 3 stainless steel 316L - 6 Monel
Pressure ranges	0 – 0.6 bar to 0 – 1600 bar
Data sheet	1202



**RChg 80  
RChgG 80**

Case / ring	crimped-on ring case stainless steel
Case filling	without / with
Accuracy	class 1.6 class 2.5 (at 0 – 600 bar and 0 – 1000 bar)
Nominal size	80 mm
Wetted parts	- 1 brass - 3 stainless steel 316L
Pressure ranges	0 – 0.6 bar to 0 – 1000 bar
Data sheet	1203



**RCh 63<sup>1)</sup>  
RChG 63<sup>1)</sup>**

Case / ring	bayonet ring case stainless steel
Case filling	without / with
Accuracy	class 1.6 class 2.5 (at 0 – 600 bar and 0 – 1000 bar)
Nominal size	63 mm
Wetted parts	- 1 brass - 3 stainless steel 316L - 6 Monel
Pressure ranges	0 – 0.6 bar to 0 – 1000 bar
Data sheet	1211



**RChg 63<sup>1)</sup>  
RChgG 63<sup>1)</sup>**

Case / ring	crimped-on ring case (polished) stainless steel
Case filling	without / with
Accuracy	class 1.6 class 2.5 (at 0 – 600 bar and 0 – 1000 bar)
Nominal size	63 mm
Wetted parts	- 1 brass - 3 stainless steel 316L - 6 Monel
Pressure ranges	0 – 0.6 bar to 0 – 1000 bar
Data sheet	1212

<sup>1)</sup> – 3v welded construction type available

## Standard Pressure Gauges



**RChg 40 - 3v**  
**RChgG 40 - 3v**

Case / ring	crimped-on ring case (polished) stainless steel
Case filling	without / with
Accuracy	class 1.6 class 2.5 (at 0 - 600 bar)
Nominal size	40 mm
Wetted parts	- 3 stainless steel 316L
Pressure ranges	0 - 1 bar to 0 - 600 bar
Data sheet	1221



**RChg 50 - 3v**  
**RChgG 50 - 3v**


Case / ring	crimped-on ring case (polished) stainless steel
Case filling	without / with
Accuracy	class 1.6 class 2.5 (at 0 - 600 bar)
Nominal size	50 mm
Wetted parts	- 3 stainless steel 316L
Pressure ranges	0 - 1 bar to 0 - 600 bar
Data sheet	1231



**RChg 50 - 3**  
**RChgG 50 - 3**

Case / ring	crimped-on ring case (polished) stainless steel
Case filling	without / with
Accuracy	class 1.6 class 2.5 (at 0 - 600 bar)
Nominal size	50 mm
Wetted parts	- 3 stainless steel 316L
Pressure ranges	0 - 1 bar to 0 - 600 bar
Data sheet	1232


## Safety Pressure Gauges



**Safety Version**

**RSCh 63  
RSChG 63**

Case / ring	bayonet ring case stainless steel
Case filling	without / with
Accuracy	class 1.6 class 2.5 (at 0 – 600 bar and 0 – 1000 bar)
Nominal size	63 mm
Wetted parts	- 1 brass - 3 stainless steel 316L - 6 Monel
Pressure ranges	0 – 0.6 bar to 0 – 1000 bar
Data sheet	1610



**Safety Version**

**RSCh / RSChG**


Case / ring	bayonet ring case stainless steel
Case filling	without / with
Accuracy	class 1.0
Nominal size	100, 160 mm
Wetted parts	- 1 brass - 3 stainless steel 316L - 6 Monel
Pressure ranges	0 – 0.6 bar to 0 – 1600 bar <sup>1)</sup>
Data sheet	1600



**Safety Version**

**RSChG 160 – 3v  
RSChG 160 – 3v**

Case / ring	crimped-on ring case stainless steel
Case filling	without / with
Accuracy	class 1.0
Nominal size	160 mm
Wetted parts	- 3 stainless steel 316L
Pressure ranges	0 – 0.6 bar to 0 – 1600 bar <sup>1)</sup>
Data sheet	1602



**High Pressure Gauge  
According to DIN 16001**

**RSCh / RSChG**

Specifics	break-proof solid front, blow-out back, bottom high- pressure connection for 1/4" tube, with 60° sealing cone, female thread M 16x1.5 or 3/16" – 18 UNF
Case / ring	bayonet ring case stainless steel
Case filling	without / with
Accuracy	class 1.0
Nominal size	100, 160 mm
Wetted parts	- 3 stainless steel 316L
Pressure ranges	0 – 2000 bar to 0 – 6000 bar
Data sheet	1640

<sup>1)</sup> pressure ranges > 1600 bar according to DIN 16001 (see data sheet 1640)

## Special Pressure Gauges



**Square Gauge**

**RQS**

Specifics	square case front narrow rim for the installation into switch panels and control panels
Case / ring	square case galvanised steel black
Case filling	without / with
Accuracy	class 1.0
Nominal size	96, 144 mm
Wetted parts	- 1 brass - 3 stainless steel 316L
Pressure ranges	0 – 0.6 bar to 0 – 1000 bar
Data sheet	1500



**Caisson Gauge**

**RCaiCh 160**

Specifics	holding chain stainless steel, adjustable pointer, 2 bottom vents
Case / ring	bayonet ring case stainless steel
Case filling	without
Accuracy	class 1.0
Nominal size	160 mm
Wetted parts	- 1 brass
Pressure ranges	0 – 0.6 bar to 0 – 16 bar
Data sheet	1800



**Process Gauge**

**RPG / RPPG 4 1/2"**

Specifics	break-proof solid front, blow-out back, integrated rear flange US Standard Process Gauge
Case / ring	plastic screw ring PBTP (thermoplastic)
Case filling	without / with
Accuracy	Grade 2A according to ASME B40.1 (0.5 %)
Nominal size	4 1/2"
Wetted parts	- 3 stainless steel 316L - 6 Monel
Pressure ranges	0 – 0.6 bar to 0 – 1000 bar
Data sheet	1401



**Subsea Gauge**

**RChG 100 – 3  
RChG 160 – 3**

Specifics	IP68, application to a water depth of 3000 m (10000 ft) dial aluminum black, scale white
Case / ring	bayonet ring case stainless steel
Case filling	with
Accuracy	class 1.0
Nominal size	100, 160 mm
Wetted parts	- 3 stainless steel 316L
Pressure ranges	0 – 0.6 bar to 0 – 1600 bar
Data sheet	1810

## Special Pressure Gauges



**Ultrapure Gas Pressure Gauge with ECD Quality**

**RCh 63**

Specifics	connection 1/4" NPT or VCR-F, VCR-M or VCR-M compact, for VCR connection increased surface finish in the inlet port, R <sub>a</sub> 0.2 – 0.4 μm
Case / ring	bayonet ring case stainless steel
Accuracy	class 1.6
Nominal size	63 mm
Wetted parts	- 3 stainless steel 316L
Pressure ranges	0 – 0.6 bar to 0 – 250 bar
Data sheet	1211



**Ultrapure Gas Pressure Gauge with ECD Quality and Safety Version**

**RSCh 63**

Specifics	connection 1/4" NPT or VCR-F, VCR-M or VCR-M compact, for VCR connection increased surface finish in the inlet port, R <sub>a</sub> 0.2 – 0.4 μm
Case / ring	bayonet ring case stainless steel
Accuracy	class 1.6
Nominal size	63 mm
Wetted parts	- 3 stainless steel 316L
Pressure ranges	0 – 0.6 bar to 0 – 250 bar
Data sheet	1610



**Can Puncturing Gauge**

**RCh 63**

Specifics	bottom connection with cannula connection, needle Ø 5 mm, rubber seal NBR
Case / ring	bayonet ring case stainless steel
Accuracy	class 1.6
Nominal size	63 mm
Wetted parts	- 1 brass
Pressure ranges	-1 / 0, -1 / 0.6, -1 / 1.5 bar
Data sheet	1211, T01-000-022

## Special Pressure Gauges



**Combi Gauges for Rail Cars**

**Rg...Fz / RChg...Fz**

**Specifics** combi gauge according to DIN 38030:2022-10 with u-clamps for panel mounting and with direct and indirect lighting as combi gauges

**Case / ring** crimped-on ring case galvanised or stainless steel crimped-on ring aluminum black anodised

**Accuracy** class 1.6 (NCS 60)  
class 1.0 (NCS 80, 100)

**Nominal size** 60, 80, 100 mm

**Wetted parts** - 1 brass

**Pressure ranges** 0 - 6, 0 - 10, 0 - 12 bar

**Data sheet** 1901



**Combi Gauges for Rail Cars**

**RChg 125 - 1 Fz**

**Specifics** combi gauge according to DIN 38030:2022-10 with u-clamps for panel mounting and with direct and indirect lighting as combi gauges special nominal size 125

**Case / ring** crimped-on ring case stainless steel crimped-on ring aluminum black anodised

**Accuracy** class 1.0

**Nominal size** 125 mm

**Wetted parts** - 1 brass

**Pressure ranges** 0 - 6, 0 - 10, 0 - 12 bar

**Data sheet** 1901.1



**SF<sub>6</sub> Gas Density Monitor**

**RChg / RChgOe / RChgN 100 - 3 SF6**

**Case / ring** crimped-on ring case stainless steel

**Case filling** RChg - without RChgOe - special oil RChgN - nitrogen

**Accuracy** class 1.0 at +20 °C (NCS 100)  
class 2.5 at -20 / +60 °C

**Nominal size** 100 mm

**Wetted parts** - 3 stainless steel 316L

**Pressure ranges** e.g. -0.1 / +0.9 MPa

**Data sheet** 1902



**SF<sub>6</sub> Gas Density Monitor**

**RChgN 63 - 3 SF6**

**Case / ring** crimped-on ring case stainless steel

**Case filling** RChgN - nitrogen

**Accuracy** class 1.0 at +20 °C  
class 2.5 at -20 / +60 °C

**Nominal size** 63 mm

**Wetted parts** - 3 stainless steel 316L gas-shielded arc welding, leakage rate < 10<sup>-9</sup> mbar l/s

**Pressure ranges** spans 2.5 to 16 bar gauge or absolute pressure

**Industry Brochure** SF6



**SF<sub>6</sub> Gas Density Indicator**

**RChg 63 - 3 r SF6**

**Case / ring** crimped-on ring case stainless steel

**Case filling** RChg - without

**Accuracy** class 1.0 at +20 °C  
class 2.5 at -20 / +60 °C

**Nominal size** 63 mm

**Wetted parts** - 3 stainless steel 316L gas-shielded arc welding, leakage rate < 10<sup>-9</sup> mbar l/s

**Pressure ranges** spans 1.6 to 16 bar gauge or absolute pressure

**Industry Brochure** SF6

## Low Cost Pressure Gauges



**RE 40 - 1**  
**RE 50 - 1**

Case / ring	steel case black
Window	snap-in polycarbonate
Accuracy	class 1.6
Nominal size	40, 50 mm
Wetted parts	- 1 brass
Pressure ranges	0 - 1 bar to 0 - 400 bar
Data sheet	1132



**RE 63 - 1**

Case / ring	steel case black
Window	snap-in polycarbonate
Accuracy	class 1.6 class 2.5 (at 600 bar)
Nominal size	63 mm
Wetted parts	- 1 brass
Pressure ranges	0 - 0.6 bar to 0 - 600 bar
Data sheet	1110



**RE 100 - 1**

Case / ring	steel case black
Window	snap-in polycarbonate
Accuracy	class 1.6
Nominal size	100 mm
Wetted parts	- 1 brass
Pressure ranges	0 - 0.6 bar to 0 - 600 bar
Data sheet	1120




**RgG 63 - 1**

Case / ring	crimped-on ring case stainless steel
Case filling	with
Accuracy	class 1.6
Nominal size	63 mm
Wetted parts	- 1 brass
Pressure ranges	0 - 1 bar to 0 - 600 bar
Data sheet	1112



## Chemical Seal Mounting

Chemical seals extend the fields of application of measuring instruments for pressure, vacuum, compound ranges, and absolute pressure, i.e. Bourdon tube pressure gauges, pressure transmitters and others. Here, pressure ranges of just a few mbar up to 1000 bar and higher can be realised. Chemical seals can be mounted directly, or via cooling element / capillary line between chemical seal and measuring instrument.



Basically, chemical seals consist of a body with process connection and a diaphragm as separating element, which prevents the medium from entering the measuring unit. Especially for media that are toxic and environmentally damaging, or if the corrosion resistance of the wetted parts has to be guaranteed, the application of chemical seals is inevitable. Chemical seals are also used if processes and regulations set particularly high hygienic standards, e.g. in food, bio and pharmaceutical industries (free of medium wetted dead spaces). For some process connections, certifications according to 3-A and / or EHEDG are available.

## Welded Connections – DW-Line (Double Weld)




**RCh 63 – 3 vDW**  
**RChG 63 – 3 vDW**

Case / ring	bayonet ring case stainless steel welded
Case filling	without / with
Accuracy	class 1.6 class 2.5 for pressure ranges 0 – 600 bar
Nominal size	63 mm
Wetted parts	stainless steel
Pressure ranges	0 – 1 bar to 0 – 600 bar
Data sheet	1211.7



**RCh / RChG**  
**– 3 vDW**

Case / ring	bayonet ring case stainless steel welded
Case filling	without / with
Accuracy	class 1.0
Nominal size	100, 160 mm
Wetted parts	stainless steel
Pressure ranges	0 – 0.6 bar to 0 – 600 bar
Data sheet	1201.7



- ◆ Pressure gauge welded with chemical seal – not screwed
- ◆ No external filling orifices – leakage cannot occur
- ◆ Parts are easy to clean externally

## Additional Electrical Accessories

Additional electrical accessories can be integrated in Bourdon tube pressure gauges. Limit switch contact assemblies close or open electric or pneumatic circuits. With the adjustable pointer and the key, the limit setting pointers can be adjusted to the required value on the entire range of the scale. When exceeding or falling below the adjusted reference value, the actual value pointer triggers the switch.



With Limit Switch

**RCh / RChOe**


Case / ring	bayonet ring case stainless steel	
Nominal size	100, 160 mm	
Additional electrical accessory type	low-action contact	S
	magnetic contact	M
	electronic contact	E
	inductive contact	I
	pneumatic contact	P
Degree of protection	IP54	
	IP65 (model RChOe)	
Data sheet	1201.90	



With Limit Switch

**RSCh / RSChOe**


Specifics	safety version	
Case / ring	bayonet ring case stainless steel	
Nominal size	100, 160 mm	
Additional electrical accessory type	low-action contact	S
	magnetic contact	M
	electronic contact	E
	inductive contact	I
	pneumatic contact	P
Degree of protection	IP54	
	IP65 (model RSChOe)	
Data sheet	1600.90	



With Limit Switch

**RQS**


Specifics	square case	
Case / ring	front narrow rim steel black	
Nominal size	96, 144 mm	
Additional electrical accessory type	low-action contact	S
	magnetic contact	M
	electronic contact	E
	inductive contact	I
	pneumatic contact	P
Degree of protection	-	
Data sheet	1500.90	



With Magnetic Contact

**RSCh 63**


Specifics	safety version	
Case / ring	bayonet ring case stainless steel	
Nominal size	63 mm	
Additional electrical accessory type	magnetic contact	M
Degree of protection	IP54	
Data sheet	1610.91	



With Inductive / Electronic Contact

**RSCh 63**

Specifics	safety version	
Case / ring	bayonet ring case stainless steel	
Nominal size	63 mm	
Additional electrical accessory type	electronic contact	E
	inductive contact	I
Degree of protection	IP54	
Data sheet	1610.92	



With Reed Contact

**RSCh 63**

Specifics	safety version	
Case / ring	bayonet ring case stainless steel	
Nominal size	63 mm	
Additional electrical accessory type	reed contact	R
Degree of protection	IP54	
Data sheet	1610.94	

## Enquiries and Orders

We are pleased to offer our help and answer any of your questions and provide background information on our pressure gauges. We can only optimise the measuring instrument for your specific case of application when receiving exact, complete information on the process or a precise specification of the required measuring system.

We have prepared checklists for you to help you with the specification of your instruments.

PDF versions as fillable document and for printing can be found at [www.armano-messtechnik.com](http://www.armano-messtechnik.com) (Downloads / Checklists).



**Checklist Pressure Gauges**

**ARMANO**  
Heading 1 - 4, 6

Inquiry / Project / Order No. \_\_\_\_\_ Name / Address / Phone / E-Mail \_\_\_\_\_ Date \_\_\_\_\_

Application (short description) \_\_\_\_\_

Medium  liquid  gas \_\_\_\_\_

Operating pressure \_\_\_\_\_ bar / dynamic from \_\_\_\_\_ to \_\_\_\_\_ bar / frequency \_\_\_\_\_ Hz

Outdoor use  yes  no

Ambient temperature from \_\_\_\_\_ °C to \_\_\_\_\_ °C

Medium temperature from \_\_\_\_\_ °C to \_\_\_\_\_ °C

Vibration  yes  no

Measuring system  piezo  other \_\_\_\_\_

Accounting class  0.25  0.5  1.0  1.6  2.5 \_\_\_\_\_

Case material  stainless steel  plastic  other \_\_\_\_\_

Case model \_\_\_\_\_

Window  clear ring w/o mirror  ring  square case  other \_\_\_\_\_

Blow-out  yes  no

Case filling  yes  no

Nominal case size (NCS)  63 (1.5)  80 (2)  100 (2.5)  125 (3)  160 (4) \_\_\_\_\_

Wetted parts  316L (1.4571)  316 (1.4308)  304 (1.4308)  304L (1.4306)  309S (1.4876)  310S (1.4928)  314 (1.4324)  314L (1.4328)  316Ti (1.4529)  316L Ti (1.4571)  316L Ti (1.4571)  316L Ti (1.4571) \_\_\_\_\_

Position of connection  1/2"  1/4"  1/8" \_\_\_\_\_

Mounting  direct mounting  back flange for surface mounting (B)  other \_\_\_\_\_

Pressure range  0-1 bar  0-2 bar  0-3 bar  0-4 bar  0-5 bar  0-6 bar  0-10 bar  0-16 bar  0-25 bar  0-40 bar  0-60 bar  0-100 bar  0-160 bar \_\_\_\_\_

Private connection  yes  no

Restrictor screw  no  yes, order \_\_\_\_\_

Additional accessories  limit switches, digital indicators, higher coverage protection \_\_\_\_\_

Installation for Ex-Zone  no  yes, order \_\_\_\_\_

Certificates  certificate of compliance to EX  certificate of compliance to 2.1 DIN EN 10 204  certificate of compliance to 2.2 DIN EN 10 204 \_\_\_\_\_

Accuracy  0.25  0.5  1.0  1.6  2.5 \_\_\_\_\_

ARMANO Messtechnik GmbH  
Ludwig-Messner-Strasse 11 • 42699 Solingen  
Tel. +49 201 8716 10-12 Fax +49 201 8716 10-13 www.armano-messtechnik.com



With Reed Contact

### RCh 63

Case / ring	bayonet ring case stainless steel
Nominal size	63 mm
Additional electrical accessory type	reed contact R
Degree of protection	IP54
Data sheet	1211.94



With Integrated Pressure Transmitter DMU

### RSCh / RSChOe

Specifics	safety version
Case / ring	bayonet ring case stainless steel
Nominal size	100, 160 mm
Additional electrical accessory type	pressure transmitter piezoresistive sensor thin film sensor
Degree of protection	IP54 IP55 (model RSChOe)
Data sheet	9631

## Any Questions? Contact Us!

Our agencies worldwide and in Germany:





**ARMANO**

**ARMANO Messtechnik GmbH**

**Location Beierfeld**

Am Gewerbepark 9  
08344 Grünhain-Beierfeld  
Germany

Tel.: +49 3774 58 - 0

Fax: +49 3774 58 - 545

mail@armano-beierfeld.com

**Location Wesel**

Manometerstraße 5  
46487 Wesel-Ginderich  
Germany

Tel.: +49 2803 9130 - 0

Fax: +49 2803 1035

mail@armano-wesel.com

**Subsidiary Company**

**ARMANO Instruments, Inc.**

14900 Woodham Drive, Suite A-150  
Houston, Texas 77073  
USA

Tel.: +1 281 982 3333

mail@armano-instruments.com

www.armano-instruments.com

Copyright© 2023 · Overview 1000 – Bourdon Tube Pressure Gauges – Mechanical Pressure Measuring Instruments (Version 10/23)

Concept, Design and Realisation: ARMANO Messtechnik GmbH · Picture credits: www.stock.adobe.com  
Technical changes, replacement of materials and printing errors excepted!